













Description										
<b>Terminal</b>	<b>MarineStar</b>	<b>SeaStar Wi-Fi</b>	<b>Atlas IP</b>	<b>Orion IP</b>	<b>Cobham Sailor Fleet One Wi-Fi</b>	<b>Cobham Sailor 250 FleetBroadband</b>	<b>Cobham Sailor 500 FleetBroadband</b>	<b>Iridium GO! with Marine Antenna</b>	<b>Cobham Sailor 4300</b>	<b>Thales VesseLink 350</b>
<b>Coverage Area</b>	Europe, Africa, Asia, Oceania	Europe, Africa, Asia, Oceania	Europe, Africa, Asia, Oceania	Europe, Africa, Asia, Oceania	Global excluding Poles	Global excluding Poles	Global excluding Poles	Global excluding Poles	Global	Global
<b>Control Unit</b>	203x190x72.7 mm 1.07 kg	210x205x85 mm 1.2 kg	293x243x68 mm 2.9 kg	281x233x46 mm 2.2 kg	297x228x77 mm 2.8 kg	273x264,5x42.5 mm 2.5 kg	273x264,5x42.5 mm 2.5 kg	114x83x32 mm 305 g	300x230x76 mm 3.5 kg	300x230x76 mm 3.4 kg
<b>Antenna</b>	marine omnidirectional Ø 185 mm; h 170 mm 1.3 kg	marine omnidirectional Ø 164 mm; h 170 mm 1.1 kg	marine gyroscopic self-calibration Ø 324 mm; h 278 mm 3.0 kg	marine gyroscopic self-calibration Ø 319 mm; h 277 mm 4.0 kg	marine gyroscopic self-calibration Ø 275.6 mm; h 292 mm 3.9 kg	marine gyroscopic self-calibration Ø 275 mm; h 329 mm 4.2 kg	marine gyroscopic self-calibration Ø 687 mm; h 795.5 mm 19.0 kg	marine passive omnidirectional Ø 95 x h 150 mm 264 g	marine omnidirectional Ø 380 mm; h 370 mm 9.5 kg	marine gyroscopic self-calibration Ø 368 mm; h 198 mm 3.2 kg
<b>Telephone</b>	YES	YES	YES	NO	YES	YES	YES	NO	NO	NO
<b>Functionality</b>	Voice, SMS and data* *(only with RS232 serial port)	Voice, SMS and data	Voice, SMS and data	Data	Voice, SMS and data	Voice, SMS and data	Voice, SMS and data	Voice, SMS and data only via App	Voice and data	Voice and data
<b>Data Shared (uplpad/download)</b>	GmPRS 15/60 kbps	GmPRS 15/60 kbps	404/444 kbps	404/444 kbps	150/150 kbps	284/284 kbps	432/432kbps	Dial-up 2.4 kbps	176/704 kbps	352/704 kbps
<b>Data Streaming (uplpad/download)</b>	NO	NO	up to 384/384 kbps	up to 384/384 kbps	NO	fino a 128/128 kbps	fino a 256/256 kbps	NO	up to 256/256 kbps	up to 256/256 kbps
<b>Battery</b>	NO	NO	NO	NO	NO	NO	NO	Li-ion 3,600 mAh	NO	NO
<b>Power Supply</b>	10.8-31.5 V DC	10.8-31.2 V DC	10-32 V DC	10-32 V DC	10.8-31.2 V DC	10,5-32 V DC	10,5-32 V DC	12-24 V DC	10.8-31.2 V DC	10-32 V DC
<b>Connectivity</b>	RS232 Serial Port	Wi-Fi IEEE 802.11 b/g/n Ethernet	Wi-Fi IEEE 802.11 b/g Ethernet	Wi-Fi IEEE 802.11 b/g/n Ethernet	Wi-Fi IEEE 802.11 b/g/n Ethernet	Ethernet	Ethernet	Wi-Fi	Ethernet	Wi-Fi IEEE 802.11 b/g Ethernet
<b>Environmental Protection Rate Antenna</b>	IP66	IP66	IP56	IP56	IPX6	IPX6	IPX6	IP65	IPX6	IP67
<b>Package</b>	MarineStar: control unit, antenna; mounting kit, power supply cable, GPS cable (TNC) 25 m, SAT cable (N) 25 m, user manual.	SeaStar Wi-Fi: control unit, antenna; mounting kit, power supply cable (power supply not included), GPS cable (TNC) 25 m, SAT cable (N) 25 m, USB cable (OTG), Wi-Fi router quick start guide, installation manual, user manual, Wi-Fi router.	Atlas IP: control unit, antenna, telephone; mounting kit, SAT - GPS cable (TNC) 25 m, power supply cable (power supply not included), Wi-Fi antenna, installation manual, user manual.	Orion IP: control unit, antenna; mounting kit, SAT - GPS cable (TNC) 25 m, power supply cable (power supply not included), Wi-Fi antenna, installation manual, user manual.	Cobham Sailor Fleet One Wi-Fi: control unit, antenna, telephone; mounting kit, SAT - GPS cable (TNC) 10 m, power supply cable (power supply not included), Ethernet cable, CD driver and software, Wi-Fi router quick start guide, user manual, Wi-Fi router.	Cobham Sailor Fleet 250: control unit, antenna, telephone; SAT - GPS cable (TNC) 25 m, power supply cable, Ethernet cable, driver and software CD, user manual.	Cobham Sailor Fleet 500: control unit, antenna, telephone; SAT - GPS cable (TNC) 30 m, power supply cable, Ethernet cable, driver and software CD, user manual.	Iridium GO!, battery, protective cover, Micro USB cable, 12-24 V DC car charger, travel charger with 100-240 V AC international plugs, quick guide in Italian, user manual, passive omnidirectional antenna, SAT cable (TNCN) 10m, mounting bracket, wall bracket, antenna adapter (TS9-TNC).	Cobham Sailor 4300: control unit, antenna; mounting kit, SAT - GPS cable (TNC) 25 m, power supply cable, Ethernet cable, driver and software CD, installation manual, user manual.	Thales VesseLINK: control unit, antenna; mounting kit, SAT - GPS cable (TNC) 25 m, power supply cable with USA and EURO plugs 1.8 m, Ethernet cable 3 m, Wi-Fi Antenna, installation manual, quick start guide.