











Description							
Modem	WE	IP+	IsatHub	9202	Explorer 510	9211	Explorer 710
Coverage Area	Europe, Africa, Asia and Oceania	Europe, Africa, Asia and Oceania	Global excluding Poles	Global excluding Poles	Global excluding Poles	Global excluding Poles	Global excluding Poles
Control Unit - Dimensions - Weight	230x197x24 mm 1.0 kg	216x216x45 mm 1.4 kg	179x170x30 mm 0.85 kg	216x216x51 mm 1.4 kg	202x202x52 mm 1.4 kg	232x292x51mm 1.9 kg	332x279x54 mm 3.5 kg
Functionality	Voice, SMS and dual band data (SAT e LTE/3G)	Voice (only VoIP services) and data	Voice and data	Voice and data	Data	Voice and data	Voice and data
Data Standard IP (upload/download)	384/384 kbps	404/444 kbps	240/384 kbps	448/464 kbps	464/464 kbps	492/492 kbps	492/492 kbps
Data Streaming (upload/download)	NO	up to 384/384 kbps	NO	up to 128/128 kbps	up to 128/128 kbps	up to 256/256 kbps	up to 384/384 kbps
Data HDR Streaming (upload/download)	NO	NO	NO	NO	NO	up to 650/650 kbps	up to 650/650 kbps
Battery	Li-ion	Li-ion	Li-ion	Li-ion	Li-ion	Li-ion	Li-ion
Power Supply	19 V DC	19 V DC	18 V DC	19 V DC	19 V DC	20 V DC	15 V DC
Connectivity	Wi-Fi IEEE 802.11b/g/n	Wi-Fi IEEE 802.11b/g/n Ethernet	Wi-Fi 802.11 b/g/n Ethernet	Wi-Fi IEEE 802.11b Ethernet	Wi-Fi IEEE 802.11b/g/n Ethernet	Wi-Fi IEEE 802.11b/g/n Ethernet	Wi-Fi IEEE 802.11b/g Ethernet
Environmental Protection Rate	IP54	IP55	IP65	IP55	IP66	IP55	terminal IP52 antenna IP66
Package	WE, battery, travel charger with international plugs (Input 100-240 V DC - Output 12 V DC), user manual.	IP+, battery, Ethernet cable, travel charger with international plugs (Input 100-240 V DC - Output 19 V DC), user manual.	IsatHub, battery, Micro USB cable, USB pen drive with driver and user manual, travel charger with international plugs (Input 100-240 V DC - Output 18 V DC), user manual.	9202, battery, Ethernet cable, 220 V travel charger with international plugs, driver and software CD, user manual.	Explorer 510, battery, power supply, USB cable to Ethernet converter, 220 V travel charger with international plugs, cover, driver and software CD, user manual.	9211, battery, Ethernet cable, 220 V travel charger with international plugs, driver and software CD, user manual.	Explorer 710: control unit, antenna; battery, SAT - GPS cable (TNC) 10 m, Ethernet cable, USB cable, 220 V travel charger with international plugs, driver and software CD, user manual.