



Always with you



Inmarsat
9202

HUGHES

9202 is the reliable and lightweight terminal, ideal for governmental organizations and NGOs, media, first responders, public security, health care workers and personnel involved in remote areas such as oil rigs or mines.

The terminal is the smallest among BGAN class 2 devices and supports broadband data connectivity up to 464 kbps either through the integrated multi-user Wi-Fi interface or through the Ethernet cable. It also supports ISDN, is equipped with a switch to change from voice (VoIP) to data channel, and fax calls through a two-line RJ11 plug.

It is the ideal terminal for those who need a solution with the perfect balance between excellent performance, high quality of service and low prices.

Dimensions: 216x216x51 mm

Weight: 1.4 kg

Functionality: data

Satellite Antenna: directional built-in

Display: white and black

Data transmission:

- › Standard IP 448/464 kbps (upload/download)
- › Streaming up to 128/128 kbps (upload/download)
- › ISDN 64/64 kbps (upload/download)

Battery: Li-ion

- › continuous transmission: up to 5.5 hours
- › stand-by: up to 36 hours

Power supply: 10.5 - 32 V DC

Positioning system: GPS

Connectivity: Wi-Fi, Ethernet

Connectors: SIM Card, power supply DC, RJ45, RJ14, RJ11, compass

Environmental protection rating: IP55

Operating temperature:

- › external power supply: from -25 °C to +55 °C
- › battery powered: from -5 °C to +55 °C

Humidity: 95% RH at +40 °C

Compatibility: devices with Wi-Fi/Ethernet, Windows operating systems for software upgrade



PACKAGE

- › 9202
- › Battery
- › Ethernet cable
- › 220 V travel charger with international plugs
- › Driver and software CD
- › User Manual